



SPN2324

N-Channel Enhancement Mode MOSFET

DESCRIPTION

The SPN2324 is the N-Channel logic enhancement mode power field effect transistor which is produced using super high cell density DMOS trench technology. The SPN2324 has been designed specifically to improve the overall efficiency of DC/DC converters using either synchronous or conventional switching PWM controllers. It has been optimized for low gate charge, low RDS(ON) and fast switching speed.



APPLICATIONS

- Powered System
- DC/DC Converter
- Load Switch


FEATURES

- ◆ 100V/3A,R_{DS(ON)}=310mΩ@V_{GS}= 10V
- ◆ High density cell design for extremely low RDS (ON)
- ◆ Exceptional on-resistance and maximum DC current capability
- ◆ SOT-23 package design

PIN CONFIGURATION(SOT-23)



PART MARKING



YW: Date Code



SPN2324

N-Channel Enhancement Mode MOSFET

PIN DESCRIPTION

Pin	Symbol	Description
1	G	Gate
2	S	Source
3	D	Drain

ORDERING INFORMATION

Part Number	Package	Part Marking
SPN2324S23RGB	SOT-23	24YW

※ SPN2324S23RGB : Tape Reel ; Pb – Free ; Halogen – Free

ABSOULTE MAXIMUM RATINGS (TA=25°C Unless otherwise noted)

Parameter	Symbol	Typical	Unit
Drain-Source Voltage	V _{DSS}	100	V
Gate –Source Voltage	V _{GSS}	±30	V
Continuous Drain Current(T _J =150°C)	T _A =25°C	ID	A
	T _A =70°C		
Pulsed Drain Current	I _{DM}	10	A
Power Dissipation	T _A =25°C	P _D	W
	T _A =70°C		
Operating Junction Temperature	T _J	-55/150	°C
Storage Temperature Range	T _{STG}	-55/150	°C
Thermal Resistance-Junction to Ambient	R _{θJA}	100	°C/W



SPN2324

N-Channel Enhancement Mode MOSFET

ELECTRICAL CHARACTERISTICS (TA=25°C Unless otherwise noted)


Parameter	Symbol	Conditions	Min.	Typ	Max.	Unit
Static						
Drain-Source Breakdown Voltage	V _{(BR)DSS}	V _{GS} =0V, ID=250uA	100			V
Gate Threshold Voltage	V _{GS(th)}	V _{DS} =V _{GS} , ID=250uA	1	1.5	2.5	
Gate Leakage Current	I _{GSS}	V _{DS} =0V, V _{GS} =±30V			±100	nA
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} =80V, V _{GS} =0V			1	uA
		V _{DS} =80V, V _{GS} =0V T _J =125°C			5	
On-State Drain Current	I _{D(on)}	V _{DS} ≥5V, V _{GS} =10V	3.0			A
Drain-Source On-Resistance	R _{D(S)on}	V _{GS} = 10V, ID=3A		0.26	0.31	Ω
Forward Transconductance	g _{fs}	V _{DS} =10V, ID=3A		2.4		S
Diode Forward Voltage	V _{SD}	I _S =1A, V _{GS} =0V			1.2	V
Dynamic						
Total Gate Charge	Q _g	V _{DS} =80V, V _{GS} =10V ID= 5A		9	13	nC
Gate-Source Charge	Q _{gs}			2		
Gate-Drain Charge	Q _{gd}			1.4		
Input Capacitance	C _{iss}	V _{DS} =25, V _{GS} =0V f=1MHz		508		pF
Output Capacitance	C _{oss}			29		
Reverse Transfer Capacitance	C _{rss}			16.5		
Turn-On Time	t _{d(on)}	V _{DD} =50V, R _L =10Ω ID=3A, V _{GEN} =10V R _G =3.3Ω		2		nS
	t _r			21.5		
Turn-Off Time	t _{d(off)}			11.2		
	t _f			18.8		




SPN2324

N-Channel Enhancement Mode MOSFET


TYPICAL CHARACTERISTICS




Output Characteristics



Capacitance



Gate Charge




On-Resistance vs. Junction Temperature




SPN2324

N-Channel Enhancement Mode MOSFET


TYPICAL CHARACTERISTICS



On Resistance vs Gate-Source Voltage



Source-Drain Forward Diode Voltage




Normalized Thermal Transient Impedance, Junction to Foot



SPN2324

N-Channel Enhancement Mode MOSFET

SOT-23 PACKAGE OUTLINE



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.200	0.035	0.043
A1	0.000	0.100	0.000	0.004
A2	0.900	1.100	0.035	0.039
b	0.300	0.500	0.012	0.020
c	0.080	0.150	0.003	0.006
D	2.800	3.000	0.110	0.118
E	1.200	1.400	0.047	0.055
E1	2.250	2.550	0.089	0.100
e	0.950 TYP		0.037 TYP	
e1	1.800	2.000	0.071	0.079
L	0.550 REF		0.022 REF	
L1	0.300	0.500	0.012	0.020
theta	0°	8°	0°	6°



SPN2324

N-Channel Enhancement Mode MOSFET

Information provided is alleged to be exact and consistent. SYNC Power Corporation presumes no responsibility for the penalties of use of such information or for any violation of patents or other rights of third parties which may result from its use. No license is granted by allegation or otherwise under any patent or patent rights of SYNC Power Corporation. Conditions mentioned in this publication are subject to change without notice. This publication surpasses and replaces all information previously supplied. SYNC Power Corporation products are not authorized for use as critical components in life support devices or systems without express written approval of SYNC Power Corporation.

© The SYNC Power logo is a registered trademark of SYNC Power Corporation

© 2004 SYNC Power Corporation – Printed in Taiwan – All Rights Reserved

SYNC Power Corporation

7F-2, No.3-1, Park Street

NanKang District (NKSP), Taipei, Taiwan, 115, R.O.C

Phone: 886-2-2655-8178

Fax: 886-2-2655-8468

© <http://www.syncpower.com>